



Restorit®

UHS MAINTAINER

TM

DATA TECH SHEET

PRODUCT DESCRIPTION:

Restorit® is a multi-purpose floor finish maintainer designed for high speed maintenance programs. It may be used with a mop and bucket or with an autoscrubber. **Restorit®** rejuvenates the finish to produce the wet look and prolongs the life of your finish.

FEATURES:

Maintains A Wet Look Gloss:

Prolongs the finish's life when applied regularly after cleaning.

Easy To Apply:

The finish is restored as easy as damp mopping.

Dual Use:

Use as a mop-on restorer or as a cleaner in the autoscrubber.

“Pops” The Gloss:

The finish gleams after high speed buffing.

PRODUCT SPECIFICATIONS:

pH (concentrate)	9.55 ± 0.25
Appearance	Milky Light Green
Fragrance	Polymeric
Solids	7.3 ± 0.2
Freezing Point	About 32°F
Solubility in Water	Complete
Flash Point	None
Coverage	4,000 to 20,000 sq. ft. per gallon

Slip Resistance: Static coefficient of friction (James Machine) meets or exceeds 0.5 as determined by ASTM D2047-82.

INGREDIENTS:

Water	7732-18-5
Styrene acrylate copolymer	25085-34-1
Dipropylene glycol methyl ether ...	34590-94-8
Ethylene glycol	107-21-1
Modified melamine resin	68002-20-0

DILUTIONS	HEALTH		FLAMMABILITY		REACTIVITY	
CONCENTRATE CONCENTRAR	NFPA 1	HMIS	NFPA 0	HMIS	NFPA 0	HMIS
(1:4 RATIO) (1:4 RAZON)	NFPA 0	HMIS	NFPA 0	HMIS	NFPA 0	HMIS
(1:20 RATIO) (1:20 RAZON)	NFPA 0	HMIS	NFPA 0	HMIS	NFPA 0	HMIS
PROPORCIÓN	SALUD		INFLAMABILIDAD		REACTIVIDAD	
	0	1	2	3	4	
Minimal	Slight	Moderate	Serious	Severe		
Minimo	Minimo	Moderar	Grave	Drastico		

Restorit® UHS MAINTAINER

DIRECTIONS

USE INFORMATION:

Always dust mop floor first. Remove gum, labels and other attached soil deposits with a putty knife or long handled scraper. For best results preclean the floor with Franklin Compare.

AUTOSCRUB APPLICATION




CAUTION



1. DILUTE



2. SCRUB



3. BURNISH


MOP-ON APPLICATION




CAUTION



1. DILUTE



2. APPLY



3. BURNISH

AUTOSCRUB APPLICATION

1. **DILUTE** Restorit® at 6 ounces per gallon (1:20 ratio) of cool water in the solution tank.
2. **AUTOSCRUB:** Apply solution and scrub with a red or white pad. Squeegee up excess solution from the floor and allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

MOP-ON APPLICATION

1. **DILUTE** Restorit® at 32 ounces per gallon (1:4 ratio) of cool water.
2. **APPLY** solution with a clean mop. Change solution when it becomes dirty. No rinsing required. Allow to dry thoroughly.
3. **BURNISH** as desired to "pop-the-gloss".

FIRST AID:

If in eyes or on skin, immediately flush with plenty of water. Get medical attention if irritation persists. **If swallowed,** get medical attention. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

HANDLING AND STORAGE:

SUGGESTED STORAGE TEMPERATURE: Store inside at 40-90°F. **SPECIAL HANDLING AND STORAGE:** Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Store in a cool, dry, ventilated area. **Protect from freezing.** Thoroughly rinse empty containers. **KEEP OUT OF REACH OF CHILDREN.**

PERSONAL PROTECTION:

Respiratory Protection: Not needed under normal conditions.
Ventilation: Use with adequate ventilation.
Eye Protection: Safety glasses are optional.
Protective Gloves: Safety gloves are optional.
Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

TRANSPORTATION INFORMATION:

U.S. DOT - Proper Shipping Name: Not Regulated by DOT.
Marine Pollutant: No

MSDS FAX RETRIEVAL
Read MSDS before using this product

800-551-0101

OBTENCIÓN DE HDSM POR FAX
Leer la HDSM antes de utilizar este producto

FOR CHEMICAL EMERGENCY,
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT
CALL CHEMTREC DAY OR NIGHT

800-424-9300

PARA EMERGENCIAS QUÍMICA DERRAMES,
ESCAPES, FUEGO, EXPOSICIÓN O ACCIDENTE
LLAMAR DE DÍA O DE NOCHE A CHEMTREC

TECH HOTLINE
800-810-4829
LINEA DE TÉCNICA